

CLMPTO 09/24/04 JW

Amend Claims 2,4,5,8-11,13-16,18, 20-27, 29-32,34,36-48

Cancel Claims 1,17,33,

1. (Cancelled)

2. (Currently Amended) The apparatus of claim 1, A base station node of a radio access network which determines a number of connections for each of plural spreading factors that can be added to the base station node, and which sends to a radio network controller (RNC) node a capacity indication including a capacity value based on the determined number of connections, wherein the capacity indication includes a vacancy capacity value for each of plural spreading factors.

3. (Original) The apparatus of claim 2, wherein the capacity indication includes a number of connections that can be added at the base station for each of plural spreading factors.

4. (Currently Amended) The apparatus of claim 2, A base station node of a radio access network which determines a number of connections for each of plural spreading factors that can be added to the base station node, and which sends to a radio network controller (RNC) node a capacity indication including a capacity value based on the determined number of connections, wherein the capacity indication is a total capacity value calculated using a vacancy capacity value for each of plural spreading factors.

5. (Original)(Currently Amended) The apparatus of claim 4, wherein the capacity indication is determined at least in part using the following ~~expression~~ expression 5:

$$R = \sum_{i=1}^{SF} W_i \cdot A_i \cdot C_i$$

wherein:

R = the required

5

W_d = a weighting factor for spreading factor sf;

A_d = number of connections that can be added with spreading factor sf;

C_d = consumption for spreading factor sf according to reported consumption

law.

6. (Originally/Currently Amended) The apparatus of claim 4, wherein the capacity indication is determined at least in part using the following expression: ~~Expression 6;~~

$$P = \sum_i \frac{W_d}{N} \cdot A_d \cdot C_d$$

wherein:

P = free resources;

W_d = a weighting factor for spreading factor sf;

A_d = number of connections that can be added with spreading factor sf;

C_d = consumption for spreading factor sf according to reported consumption

law.

7. (Originally/Currently Amended) The apparatus of claim 6, wherein the capacity indication is determined using the following expression: ~~Expression 7;~~

$$Cap_{sf} = L + P$$

wherein:

P = free resources;

L = load;

8. (Currently Amended) The apparatus of claim 4 or 6, wherein the base station tracks usage of base station resources for determining the number of connections that can be added to the base station node.

9. (Currently Amended) The apparatus of claim 4 or 6, wherein the capacity indication reports the determined number for a particular spreading factor utilized at the base station node.

Art Unit: 2600

10. (Currently Amended) The apparatus of claim 2 or 4, wherein the capacity indication reports the determined number separately for uplink transmissions and downlink transmissions relative to the base station node.

11. (Currently Amended) The apparatus of claim 2 or 4, wherein the capacity indication reports the determined number based on a combination of free connections for each of plural spreading factors, and using consumption laws appropriate for each of the spreading factors.

12. (Original) The apparatus of claim 11, wherein the combination is a weighted combination.

13. (Currently Amended) The apparatus of claim 2 or 4, wherein the capacity indication is included in a SCPP "Resource Status Indication" message.

14. (Currently Amended) The apparatus of claim 2 or 4, wherein the capacity indication is included in a message which is distinct from a SCPP "Resource Status Indication" message.

15. (Currently Amended) The apparatus of claim 2 or 4, wherein the capacity indication is included in its own dedicated message.

16. (Currently Amended) The apparatus of claim 2 or 4, wherein the base station node has plural devices, and wherein the capacity determination is based on a number of free resources per device.

17. (Cancelled)

18. (Currently Amended) The method of claim 17, further comprising: A method of operating a radio access network, the method comprising:
determining, for each of plural spreading factors, a number of connections that can be added to a base station node; and

~~sending a capacity indication to a radio network controller (RNC) node, the capacity indication including a capacity value which is based on the determined number of connections;~~

~~including in the capacity indication as the capacity value a vacancy capacity value for each of plural spreading factors.~~

19. (Original) The method of claim 18, further comprising including in the capacity indication as the capacity value a number of connections that can be added at the base station for each of plural spreading factors.

20. (Currently Amended) The method of claim 17, further comprising A method of operating a radio access network, the method comprising:

~~determining, for each of plural spreading factors, a number of connections that can be added to a base station node; and~~

~~sending a capacity indication to a radio network controller (RNC) node, the capacity indication including a capacity value which is based on the determined number of connections;~~

~~including in the capacity indication a total capacity value calculated using a vacancy capacity value for each of plural spreading factors.~~

21. (Original)(Currently Amended) The method of claim 20, wherein the capacity value is determined at least in part using Expression 5, the following expression:

$$P = \sum_{i=1}^M W_i \cdot A_i \cdot C_i$$

wherein:

P = free resources

W_i = a weighting factor for spreading factors i

A_i = number of connections that can be added with spreading factor i

C_i = correction for spreading factor i according to reported contribution

law.

Art Unit: 2600

22. (Originally/Currently Amended) The method of claim 20, wherein the capacity value is determined at least in part using the following expression: Equation 6;

$$P = \sum_{i=1}^{N_P} \frac{W_i}{N} \cdot A_i \cdot C_i$$

wherein:

P = free resources;

W_i = a weighting factor for spreading factor i ;

A_i = number of connections that can be added with spreading factor i ;

C_i = consumption for spreading factor i according to reported consumption

info.

23. (Originally/Currently Amended) The method of claim 20, wherein the capacity value is determined using the following expression: Equation 7;

$$Cap_{max} = L + P_{max}$$

wherein:

P = free resources;

L = load.

24. (Currently Amended) The method of claim 17/claim 18 or 20, further comprising tracking at the base station tracks usage of base station resources for determining the number of connections that can be added to the base station node.

25. (Currently Amended) The method of claim 17/claim 18 or 20, wherein the capacity indication reports the determined number for a particular spreading factor utilized at the base station node.

26. (Currently Amended) The method of claim 17/claim 18 or 20, wherein the capacity indication reports the determined number separately for uplink transmissions and downlink transmissions relative to the base station node.

Art Unit: 2600

27. (Currently Amended) The method of claim 17 or 20, wherein the capacity indication reports the determined number based on a combination of free connections for each of plural spreading factors, and using consumption laws appropriate for each of the spreading factors.

28. (Original) The method of claim 27, wherein the combination is a weighted combination.

29. (Currently Amended) The method of claim 17 or 20, further comprising including the capacity indication in a 3GPP "Resource Status Indication" message.

30. (Currently Amended) The method of claim 17 or 20, further comprising including the capacity indication in a message which is distinct from a 3GPP "Resource Status Indication" message.

31. (Currently Amended) The method of claim 17 or 20, further comprising including the capacity indication in its own dedicated message.

32. (Currently Amended) The method of claim 17 or 20, wherein the base station node has plural devices, and wherein the capacity determination is based on a number of free resources per device.

33. (Cancelled)

34. (Currently Amended) The apparatus of claim 33, A radio access network for comprising:

a radio network controller (RNC) node;

a base station node connected to the radio network controller (RNC) node, the base station node determining a number of connections for each of plural spreading factors that can be added to the base station node, and which sends to a radio network controller (RNC) node a capacity indication including a capacity value based on the

Art Unit: 2600

determined number of connections, wherein the capacity value included in the capacity indication includes a vacancy capacity value for each of plural spreading factors.

35. (Original) The apparatus of claim 34, wherein the capacity value included in the capacity indication includes a number of connections that can be added at the base station for each of plural spreading factors.

36. (Currently Amended) The apparatus of claim 33, ~~a radio access network for~~ comprising:

a radio network controller (RNC) node;

a base station node connected to the radio network controller (RNC) node, the base station node determining a number of connections for each of plural spreading factors that can be added to the base station node, and which sends to a radio network controller (RNC) node a capacity indication including a capacity value based on the determined number of connections, wherein the capacity value included in the capacity indication is a total capacity value calculated using a vacancy capacity value for each of plural spreading factors.

37. (Original)(Currently Amended) The apparatus of claim 36, wherein the capacity value is determined at least in part using the following expression Expression-5:

$$P = \sum_{i=1}^M W_i \cdot A_i \cdot C_i$$

wherein:

P = free resources;

W_i = a weighting factor for spreading factor i ;

A_i = number of connections that can be added with spreading factor i ;

C_i = consumption for spreading factor i according to reported consumption

law.

38. (Original)(Currently Amended) The apparatus of claim 36, wherein the capacity value is determined at least in part using the following expression Expression-6:

$$P = \sum_{i=1}^N \frac{W_i}{N} + A_v + C_v$$

wherein:

P = free resources;

W_i = a weighting factor for spreading factor i ;

A_v = number of connections that can be added with spreading factor v ;

C_v = consumption for spreading factor v according to reported consumption law.

39. (Original)(Currently Amended) The apparatus of claim 36, wherein the capacity value is determined using the following expression: Equation 3;

$$Cap_{max} = L + P$$

wherein:

P = free resources;

L = load.

40. (Currently Amended) The apparatus of claim 33-claim 34 or 36, wherein the base station tracks usage of base station resources for determining the number of connections that can be added to the base station node.

41. (Currently Amended) The apparatus of claim 33-claim 34 or 36, wherein the capacity indication reports the determined number for a particular spreading factor utilized at the base station node.

42. (Currently Amended) The apparatus of claim 33-claim 34 or 36, wherein the capacity indication reports the determined number separately for uplink transmission and downlink transmission relative to the base station node.

43. (Currently Amended) The apparatus of claim 33-claim 34 or 36, wherein the capacity indication reports the determined number based on a combination of free

connections for each of plural spreading factors, and using consumption laws appropriate for each of the spreading factors.

44. (Currently Amended) The apparatus of claim 43, wherein the combination is a weighted combination.

45. (Currently Amended) The apparatus of claim 33-claim 34 or 36, wherein the capacity indication is included in a 3GPP "Resource Status Indication" message.

46. (Currently Amended) The apparatus of claim 33-claim 34 or 36, wherein the capacity indication is included in a message which is distinct from a 3GPP "Resource Status Indication" message.

47. (Currently Amended) The apparatus of claim 33-claim 34 or 36, wherein the capacity indication is included in its own dedicated message.

48. (Currently Amended) The apparatus of claim 33-claim 34 or 36, wherein the base station node has plural devices, and wherein the capacity determination is based on a number of free resources per device.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.